



AERODYNAMIC ABS MOULDED, CONVEX MIRROR HEADS	
Manufactured from impact resistant ABS. Complete with integral clamp to fit \varnothing 16-22mm arms. Dimensions refer to visible glass size only.	
3389/003	ABS moulded, convex mirror head.
3389/043	Convex mirror glass. 235mm (9.25") x 152mm (6"), 'E' approved, class III.
3390/003	ABS moulded, convex mirror head.
3390/043	Convex mirror glass. 331mm (13") x 214mm (8.4"), 'E' approved, class II.



'UNBREAKABLE' MIRRORS	
10 year guarantee. 85% reflection. Distortion free image. Exceeds EC directive on impact tests; withstands ball bearing shot at 120 metre per second without shattering. Withstands temperature range of -30°C to +80°C. Complete with universal fitting for 'D' or straight arms up to \varnothing 24mm.	
	A B C D E F G H
3396/0100	Class II Weight 1.04kg/2.3lb
METRIC (mm)	305 205 70 56 68
IMPERIAL (ins)	12.0 8.0 2.76 2.21 2.68
3396/0200	Class III Weight 330g/11.6oz
METRIC (mm)	150 210 44 47 56
IMPERIAL (ins)	5.91 8.27 1.73 1.85 2.21



• 'EUOWAY' MIRROR HEADS • 'EUOWAY' MIRROR HEADS •	
Nominal size = 320mm (13") x 200mm (8"). Black, pressed steel back-plate with convex glass. Multi-position adjustment with clamp to suit arms from \varnothing 13mm to \varnothing 23mm. 'E' approved, class III.	
3333/003	'Euoway' mirror head with clamp
3333/043	Convex mirror glass

* Non 'E' marked mirrors can only be used on trailers manufactured before October 1995 and on trucks registered before April 1996.



• MIRROR ASSEMBLY • MIRROR ASSEMBLY • MIRROR ASSEMBLY •	
Nominal size = 178mm (7") x 102mm (4"). Black plastic surround with convex glass and a black, poly-coated arm; 125mm (5") long with 89mm (3.5") max. throw-out Not 'E' approved.*	
2767/001	Mirror head with arm and bracket.