

Steps

UNDERFLOOR STEP

Mild steel construction with an electro-zinc plated finish. Pressed steel treadplate steps.

	A	B	C	D	E	F	G	H
5326/003	Weight 8.3kg/18.3lb							
METRIC (mm)	660	280	420	75	560	10.5		
IMPERIAL (ins)	26.0	11.0	16.5	2.95	22.0	0.41		



RETRACTABLE ACCESS STEP

Galvanised steel frame with an anodised aluminium step. Spring assisted pull-out, push-in action. Integral switch for dash mounted warning light (not included). Supplied with full fitting instructions.

	A	B	C	D	E	F	G	H
5327/001	Weight 7.58kg/16.7lb							
METRIC (mm)	550	180	178	41.0	537	272	88.0	232
IMPERIAL (ins)	21.7	7.09	7.01	1.61	21.1	10.7	3.50	9.14



MOTORISED RETRACTABLE ACCESS STEP

Electro-zinc plated, mild steel construction. Operation is via 12 volt motor, mounted in a shock resistant box. Complete with an integral switch for dash mounted warning light (not included) and is supplied with full fitting instructions along with wiring diagrams.

	A	B	C	D	E	F	G	H
5327/201	Weight 12.3kg/27.1lb							
METRIC (mm)	550	183	180	40.0	534	272	84.0	232
IMPERIAL (ins)	21.7	7.21	7.09	1.58	21.0	10.7	3.31	9.14



0458/0061	Coarse anti-slip tape	Weight 940g/2lb
	Black. 50.8mm (2") wide, 18.3m (60') roll. Self-adhesive, single side.	
0458/0067	Coarse anti-slip tape	Weight 740g/1.6lb
	Black & yellow. 50.8mm (2") wide, 18.3m (60') roll. Self-adhesive, single side.	

